



AFM-100 Harley RS232/USB Modem Module

Specification

Interface	RS232 interface for Smart Phone Systems
RS232 Connector Type	Assign by Systems
Controller	Conexant Harley with Smart DAA
Number of line	1
Telephone Jack Type	Assign by Systems
Dialing	AA mode DTMF Tone
Command	AT Command set
Line Speed Data Mode	56000/53300/50667/49333/46667/45333/42667/41333/38667/37333/34667/33333/ 3/ 30667/29333/33600/31200/28800/26400/24000/21600/19200/16800/14400/12000/ 0/ 9600/7200/4800/2400
Terminal Speed	230400/115200/57600/38400/19200/12000/9600/7200/4800/2400/1200/300bps
Operation	Asynchronous
Protocols	ITU-T:V.92/V.90/V.34/V.32bis/V.32/V.22bis/V.22/V.21, BELL:212A/103, K56flex
Operating Mode	Originate/Answer
Transmit Level	-6dBm to -15dBm -10dBm(default)
Receive Level	-10dBm to -35dBm
Error Correction	MNP4 & V.42
Data Compression	MNP5, V.42bis & V.44
Flow Control	Xon/Xoff, RTS/CTS
Temperature	Operating: -10 ~ 70°C
Humidity	Operating: 0 ~ 85%

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>