



GETTING THE MOST FROM YOUR TRACTOR!

8 & 9" PTO CHIPPERS!



Model CH9540H (72854) has the capacity you need with a powerful hydraulic feeding system. The hydraulic feed system makes chipping much easier by helping guide branches into the chipper housing.



Four reversible chipper blades mounted on a dynamically balanced disc weigh in at 275 lbs. [125kg] Maintenance and service is quick and easy with a hinged disc cover.



Model CH8540 (71854)

Model	Engine	Size (LxWxH)	Chipper Capacity	Feed System	Feed Opening	Weight (Lbs.)	3 Point Hitch	PTO
CH8540 (71854)	PTO	52"x47"x93"	8"	manual feed	9"x9"	885	Cat. 1	540 rpm
CH9540H (72854)	PTO	69"x50"x93"	9"	hydraulic	9"x9"	1300	Cat. 1	540 rpm

Option:
74898-00 Auto-Feed Kit for Model 72854

* For Use on Tractors with Engine Horsepower Ratings from 25 to 60 hp



Find a dealer near you!

Call us at 800.247.7335 or
 Log onto www.BearCatProducts.com

P.O. Box 849, West Fargo, ND 58078
 Email: sales@BearCatProducts.com
 Fax: 701.282.9522



8 & 9" PTO Chipper Specs

Models CH8540 (71854), CH9540H (72854)

76cm [30"] DIAMETER DISC

1.25" [76cm] diameter by 1.25" [3.2cm] thick rotor disc that weighs 275 lbs. [125kg]. Machined to balance. Disc turns at 1500 RPM. .75" [4.45cm] diameter rotor shaft.

FOUR CHIPPING BLADES

4 - Reversible Chipper Blades, heat treated chipper steel with a chrome content

HYDRAULIC FEED SYSTEM

Standard only on model CH9540H (72854)

White 45 cu. in. [737cc] hyd motor, 10-micron spin on filter. Self-contained system with infinite speed settings, dedicated neutral and full reverse, pump output. 25 liters/min [6.6 gal per min.] and 4HP with maximum pressure and maximum flow. Feed system operates under [1750 PSI [119atm], 3 gal. [11.4 liter] tank capacity. Single 15" [38cm] diameter top feed roller. Feed rate is 0 - 150 FPM [0-45 meters/min.].

FEED SYSTEM

15" diameter
45 degree chipping blade edge angle pulls the logs and limbs. Infeed hopper opening is 9"x9" [23cm x 23cm]. Drop-down feed tray with locking safety pin.

EASY ACCESS

The rotor is accessible through the hinged disc cover, which exposes one half of the disc for easy access to the chipping blades and for easy clean out.

HEAVY-DUTY CONSTRUCTION

9"x9" [.95cm] thick steel face plate on the disc housing; .25" [6.35mm] thick steel on the wrap around with welded construction.

INTEGRATED BLOWER

Put the chips where you want them with the dedicated blower. 360° rotatable, 8" [20cm] diameter steel tubing with adjustable spout cap allows you to put the chips where you want them the first time.

TRIPLE-BANDED BELT DRIVE FOR BETTER TRANSFER OF POWER

TELESCOPING TONGUE

Adjustable length and height. The length may be adjusted up to 45 cm [18"] with 4 pin settings on the pintle hitch. 5cm [2"] coupler hitch available as an accessory.

DIMENSIONS:

Model 71854 - Length 52" • Width 47" • Height 93"
Model 72854 - Length 69" • Width 50" • Height 93"

360 DEGREE ROTATIONAL BED

The 360 Degree, 8" discharge chute gives accurate control over the flow of chips

WEIGHTS

Model CH8540 (71854) - 885 lbs
Model CH9540H (72854) - 1300 lbs

SAFETY

- Safety chains standard
- Meets all applicable ISO and CE safety standards.



Find a dealer near you!

Call us at 800.247.7335 or
Log onto www.BearCatProducts.com

P.O. Box 849, West Fargo, ND 58078
Email: sales@BearCatProducts.com
Fax: 701.282.9522

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>